

For spray

Odor neutralizer

# Air Repair



**Air Repair** was developed to neutralise the alkaline odorous compounds of ammonia, butylamine, trimethylamine, other amines, skatole, volatile organic compounds and all other compounds of a similar nature which are associated with chemical and industrial processing and their wastes (solid and liquid), putrescible waste (household garbage), sewage treatment plants, all animal breeding and processing facilities, and most types of industrial waste.

The alkaline odorous compounds react with **Air Repair** and are neutralised of their toxic and offensive potential. **Air Repair** is safe and ecofriendly.

## Lab Tests

	after 16 hours	
	Control	Test
Ammonia 1%	59ppm	0
Amine Standard	42ppm	0

2012.05 Choongnam Univ.

	after 1 hour	
	Control	Test
Ammonia	50ppm	< 0.2
Trimethylamine	40ppm	< 0.2

2016.06.21 Korea Conformity Laboratories

Direct

Immediate

Fresh

- **Appearance** : Yellowish transparent liquid with characteristic smell
- **Uses** : Remove noxious gases and odors  
- Farms, manure, sewage, lagoons, landfills, household & industrial wastes and water treatment
- **Expiry** : 5 years

- **Ingredients** : Herbs, essential oils, organic acids, etc.
- **Dosage** : .For fogging : Dilute 1L with 100-200L water  
.For spraying : Dilute 250-1,000ml with 1,000L water  
.Direct dosing : 50-100ml with 100X water per 1,000L waste